

Track

2200, H0 MÃ©rclin K, Straight 18cm.	8	
2201, H0 MÃ©rclin K, Straight 9cm.	1	
2202, H0 MÃ©rclin K, Straight 4.5cm.	1	
2203, H0 MÃ©rclin K, Straight 3cm.	1	
2205, H0 MÃ©rclin K, Flex 90cm.	66	(Minimum number of units: 36)
2206, H0 MÃ©rclin K, Straight 16.89cm.	1	
2221, H0 MÃ©rclin K, Curve radius 36cm, angle 30°	9	
2231, H0 MÃ©rclin K, Curve radius 42.46cm, angle 30°	9	
2232, H0 MÃ©rclin K, Curve radius 42.46cm, angle 22.5°	1	
2241, H0 MÃ©rclin K, Curve radius 55.39cm, angle 30°	5	
2251, H0 MÃ©rclin K, Curve radius 61.85cm, angle 30°	5	
2258, H0 MÃ©rclin K, Crossing 9cm.	1	
2260, H0 MÃ©rclin K, Double slipswitch 16.89cm. (remote)	3	
2262, H0 MÃ©rclin K, Left turnout 16.89cm. (remote)	6	
2263, H0 MÃ©rclin K, Right turnout 16.89cm. (remote)	3	
2272, H0 MÃ©rclin K, Left turnout 22.5cm. (manual)	2	
2273, H0 MÃ©rclin K, Right turnout 22.5cm. (manual)	4	
2274, H0 MÃ©rclin K, Curve radius 90.24cm, angle 14.43°	2	
2291, H0 MÃ©rclin K, Straight transition K - M 18cm.	4	
2291, H0 MÃ©rclin M, Straight transition M - K 18cm.	4	
24922, H0 MÃ©rclin C, Straight transition K - C 18cm.	2	
5100, H0 MÃ©rclin M, Curve radius 36cm, angle 30°	12	
5105, H0 MÃ©rclin M, Straight contact 18cm.	2	
5106, H0 MÃ©rclin M, Straight 18cm.	14	
5107, H0 MÃ©rclin M, Straight 9cm.	4	
5109, H0 MÃ©rclin M, Straight 3.35cm.	2	
5129, H0 MÃ©rclin M, Straight 7cm.	4	
5200, H0 MÃ©rclin M, Curve radius 43.74cm, angle 30°	12	
5203, H0 MÃ©rclin M, (5202L). Left turnout 18cm. 24°17' (remote)	2	
5204, H0 MÃ©rclin M, (5202R). Right turnout 18cm. 24°17' (remote)	2	
5205, H0 MÃ©rclin M, Curve radius 43.74cm, angle 5°43'	4	
5207, H0 MÃ©rclin M, Double slipswitch 18cm. (remote)	2	
5208, H0 MÃ©rclin M, Straight 0.8cm.	2	
7389, H0 MÃ©rclin K, Buffer/Bumper 3.8cm.	8	
SL-86, 00/H0 Peco Streamline Code 100, Right curved turnout 12°	4	
SL-E87, 00/H0 Peco Streamline Code 100, Left curved turnout 12° (conductive frog)	1	

Track lengths

2200, H0 MÃ©rclin K, Straight 18cm.	144
2201, H0 MÃ©rclin K, Straight 9cm.	9
2202, H0 MÃ©rclin K, Straight 4.5cm.	4.5
2203, H0 MÃ©rclin K, Straight 3cm.	3
2205, H0 MÃ©rclin K, Flex 90cm.	3230.65
2206, H0 MÃ©rclin K, Straight 16.89cm.	16.89
2221, H0 MÃ©rclin K, Curve radius 36cm, angle 30°	169.65
2231, H0 MÃ©rclin K, Curve radius 42.46cm, angle 30°	200.09
2232, H0 MÃ©rclin K, Curve radius 42.46cm, angle 22.5°	16.67
2241, H0 MÃ©rclin K, Curve radius 55.39cm, angle 30°	145.01
2251, H0 MÃ©rclin K, Curve radius 61.85cm, angle 30°	161.92
2258, H0 MÃ©rclin K, Crossing 9cm.	18

2260, H0 MÃ©rklin K, Double slipswitch 16.89cm. (remote)	201.37
2262, H0 MÃ©rklin K, Left turnout 16.89cm. (remote)	201.38
2263, H0 MÃ©rklin K, Right turnout 16.89cm. (remote)	100.69
2272, H0 MÃ©rklin K, Left turnout 22.5cm. (manual)	90.46
2273, H0 MÃ©rklin K, Right turnout 22.5cm. (manual)	180.93
2274, H0 MÃ©rklin K, Curve radius 90.24cm, angle 14.43°	45.46
2291, H0 MÃ©rklin K, Straight transition K - M 18cm.	72
2291, H0 MÃ©rklin M, Straight transition M - K 18cm.	72
24922, H0 MÃ©rklin C, Straight transition K - C 18cm.	36
5100, H0 MÃ©rklin M, Curve radius 36cm, angle 30°	226.19
5105, H0 MÃ©rklin M, Straight contact 18cm.	35.2
5106, H0 MÃ©rklin M, Straight 18cm.	252
5107, H0 MÃ©rklin M, Straight 9cm.	36
5109, H0 MÃ©rklin M, Straight 3.35cm.	6.7
5129, H0 MÃ©rklin M, Straight 7cm.	28
5200, H0 MÃ©rklin M, Curve radius 43.74cm, angle 30°	274.83
5203, H0 MÃ©rklin M, (5202L). Left turnout 18cm. 24°17' (remote)	73.08
5204, H0 MÃ©rklin M, (5202R). Right turnout 18cm. 24°17' (remote)	73.08
5205, H0 MÃ©rklin M, Curve radius 43.74cm, angle 5°43'	17.46
5207, H0 MÃ©rklin M, Double slipswitch 18cm. (remote)	141.51
5208, H0 MÃ©rklin M, Straight 0.8cm.	1.6
7389, H0 MÃ©rklin K, Buffer/Bumper 3.8cm.	0
SL-86, 00/H0 Peco Streamline Code 100, Right curved turnout 12°	202.27
SL-E87, 00/H0 Peco Streamline Code 100, Left curved turnout 12° (conductive frog)	50.57
 Total track length:	 65.38 m